

(1)

1.		4.			
2.		5.		6.	10 X 42
3.	18	7.	2018-04-04	가	17,730
* “ ” “ ” , “ - ” .					
8. (,)			15.		
9. ()					
10.			16.		
11.			17.	()	
	-				
	-			-	
	()				
12.					
13.			18.		
	-				
			19.		
14.	-		20.		
	-		21.		
	()		22.		
	()		23.	-	
1. ■ 2. ■ 3. ■ : 4. ■ 5. ■					
			2024 02 20 ~ 2024 02 22		

【 3】

(3 3)

[illegible]

190mm × 268mm
(54g/m2)

【 4】 (3 3)

	2024 02 22					(1)		
(mm)	57.37	(mm)		57.35			(%)	1.46
		locked "D"					(kg/m)	18.75
	(mm)	58 (58.2)	(ton)		397.2	(mm)		
가	가	2018-04-01					(h)	17,730
		1	2	3	4	5	(m)	0
		(mm)			, ,			
		가 (1)	(2)	(3)			(+12%)	(7%)
(50)	1	57.4	57.4	57.40				
	2	57.3	57.4	57.35				
	3	57.4	57.4	57.40				
	4	57.4	57.4	57.40				
	5	57.3	57.4	57.35				
	6	57.3	57.4	57.35				
	7	57.4	57.4	57.40				
	8	57.4	57.4	57.40				
	9	57.3	57.4	57.35				
	10	57.3	57.4	57.35				
	11	57.3	57.4	57.35				
	12	57.4	57.4	57.40				
	13	57.3	57.4	57.35				
	14	57.4	57.4	57.40				
	15	57.3	57.4	57.35				
	16	57.3	57.4	57.35				
	17	57.4	57.4	57.40				
	18	57.4	57.4	57.40				
	19	57.3	57.4	57.35				
	20	57.3	57.4	57.35				
	21	57.4	57.4	57.40				
	22	57.3	57.4	57.35				
	23	57.4	57.4	57.40				
	24	57.4	57.4	57.40				
	25	57.3	57.4	57.35				

【 4】 (3 3)

		2024 02 22					(2)						
(mm)		57.36		(mm)		57.35			(%)		1.46		
				locked "D"					(kg/m)		18.75		
		(mm)		58 (58.2)		(ton)		397.2		(mm)			
가		가		2018-04-01					(h)		17,730		
				1	2	3	4	5	(m)		0		
		(mm)											
		가 (1)		(2)		(3)							
(50)	1	57.3	57.4		57.35								
	2	57.3	57.4		57.35								
	3	57.4	57.4		57.40								
	4	57.4	57.4		57.40								
	5	57.3	57.4		57.35								
	6	57.4	57.4		57.40								
	7	57.3	57.4		57.35								
	8	57.4	57.4		57.40								
	9	57.3	57.4		57.35								
	10	57.3	57.4		57.35								
	11	57.3	57.4		57.35								
	12	57.3	57.4		57.35								
	13	57.3	57.4		57.35								
	14	57.4	57.4		57.40								
	15	57.3	57.4		57.35								
	16	57.3	57.4		57.35								
	17	57.4	57.4		57.40								
	18	57.4	57.4		57.40								
	19	57.3	57.4		57.35								
	20	57.3	57.4		57.35								
	21	57.4	57.4		57.40								
	22	57.3	57.4		57.35								
	23	57.3	57.4		57.35								
	24	57.4	57.4		57.40								
	25	57.3	57.4		57.35								

190mm × 268mm
(54g/m2)

【 4】 (3 3)

	2024 02 22					(3)		
(mm)	57.38	(mm)		57.35			(%)	1.46
		locked "D"					(kg/m)	18.75
	(mm)	58 (58.2)	(ton)		397.2	(mm)		
가	가	2018-04-01					(h)	17,730
		1	2	3	4	5	(m)	0
		(mm)			, ,			
		가 (1)	(2)	(3)			(+12%)	(7%)
(50)	1	57.4	57.4	57.40				
	2	57.3	57.4	57.35				
	3	57.4	57.4	57.40				
	4	57.4	57.4	57.40				
	5	57.3	57.4	57.35				
	6	57.4	57.4	57.40				
	7	57.3	57.4	57.35				
	8	57.4	57.4	57.40				
	9	57.4	57.4	57.40				
	10	57.4	57.4	57.40				
	11	57.3	57.4	57.35				
	12	57.4	57.4	57.40				
	13	57.3	57.4	57.35				
	14	57.4	57.4	57.40				
	15	57.3	57.4	57.35				
	16	57.3	57.4	57.35				
	17	57.4	57.4	57.40				
	18	57.4	57.4	57.40				
	19	57.3	57.4	57.35				
	20	57.4	57.4	57.40				
	21	57.4	57.4	57.40				
	22	57.3	57.4	57.35				
	23	57.3	57.4	57.35				
	24	57.4	57.4	57.40				
	25	57.4	57.4	57.40				

【 4】 (3 3)

	2024 02 22					(4)		
(mm)	57.39	(mm)		57.35			(%)	1.46
		locked "D"					(kg/m)	18.75
	(mm)	58 (58.2)	(ton)		397.2	(mm)		
가	가	2018-04-01					(h)	17,730
		1	2	3	4	5	(m)	0
		(mm)			, ,			
		가 (1)	(2)	(3)			(+12%)	(7%)
(50)	1	57.4	57.4	57.40				
	2	57.4	57.4	57.40				
	3	57.4	57.4	57.40				
	4	57.4	57.4	57.40				
	5	57.3	57.4	57.35				
	6	57.4	57.4	57.40				
	7	57.3	57.4	57.35				
	8	57.4	57.4	57.40				
	9	57.4	57.4	57.40				
	10	57.4	57.4	57.40				
	11	57.4	57.4	57.40				
	12	57.4	57.4	57.40				
	13	57.3	57.4	57.35				
	14	57.4	57.4	57.40				
	15	57.4	57.4	57.40				
	16	57.4	57.4	57.40				
	17	57.4	57.4	57.40				
	18	57.4	57.4	57.40				
	19	57.3	57.4	57.35				
	20	57.4	57.4	57.40				
	21	57.4	57.4	57.40				
	22	57.4	57.4	57.40				
	23	57.3	57.4	57.35				
	24	57.4	57.4	57.40				
	25	57.4	57.4	57.40				

【 4】 (3 3)

		2024 02 22					(1)								
(mm)		40.27		(mm)		40.1		(%)		3.6					
				6*Fi(25)				(kg/m)		6.13					
		(mm)		40 (41.6)		(ton)		119.3		(mm)		2.68			
가		가		2018-04-01				(h)		17,730					
						2		3		4		5		(m)	
			(mm)												
			가 (1)		(2)		(3)								
(가)		1	41.6	40.7	41.20				4	2.25					
		2	41.4	40.9	41.60				4	1.75					
		3	41.2	41.3	41.60				4	1.0					
		4	41.3	41.7	41.80				4.5	1.25					
		5	40.9	41.1	41.30				3.25	1.0					
		6	41.8	41.1	41.50				4.5	1.75					
(50)		1	40.2	40.3	40.25										
		2	40.2	40.2	40.20										
		3	40.2	40.4	40.30										
		4	40.3	40.4	40.35										
		5	40.1	40.2	40.15										
		6	40.2	40.2	40.20										
		7	40.2	40.2	40.20										
		8	40.1	40.2	40.15										
		9	40.2	40.2	40.20										
		10	40.1	40.2	40.15										
		11	40.2	40.2	40.20										
		12	40.1	40.3	40.20										
		13	40.3	40.3	40.30										
		14	40.1	40.2	40.15										
		15	40.1	40.1	40.10										
		16	40.1	40.2	40.15										
		17	40.1	40.2	40.15										
		18	40.2	40.2	40.20										
		19	40.1	40.2	40.15										

190mm × 268mm
(54g/m2)

(50)	20	40.1	40.3	40.20			
	21	40.2	40.3	40.25			
	22	40.2	40.2	40.20			
	23	40.2	40.3	40.25			
	24	40.2	40.2	40.20			
	25	40.3	40.3	40.30			
	26	40.1	40.2	40.15			
	27	40.3	40.4	40.35			
	28	40.1	40.1	40.10			
	29	40.2	40.2	40.20			
	30	40.1	40.1	40.10			
	31	40.1	40.1	40.10			
	32	40.2	40.2	40.20			
	33	40.2	40.2	40.20			
	34	40.3	40.3	40.30			
	35	40.3	40.3	40.30			
	36	40.1	40.3	40.20			
	37	40.2	40.2	40.20			
	38	40.2	40.2	40.20			
	39	40.1	40.2	40.15			
	40	40.2	40.2	40.20			
	41	40.2	40.2	40.20			
	42	40.3	40.3	40.30			
	43	40.3	40.3	40.30			
	44	40.3	40.3	40.30			
	45	40.2	40.4	40.30			
	46	40.2	40.2	40.20			
	47	40.2	40.3	40.25			
	48	40.2	40.2	40.20			
	49	40.3	40.2	40.25			
	50	40.2	40.3	40.25			
	51	40.3	40.3	40.30			
	52	40.3	40.3	40.30			
	53	40.3	40.3	40.30			
	54	40.3	40.4	40.35			
	55	40.2	40.4	40.30			

190mm × 268mm
(54g/m2)

(50)	56	40.3	40.3	40.30			
	57	40.3	40.4	40.35			
	58	40.3	40.3	40.30			
	59	40.3	40.4	40.35			
	60	40.2	40.3	40.25			
	61	40.3	40.4	40.35			
	62	40.3	40.4	40.35			
	63	40.3	40.4	40.35			
	64	40.3	40.3	40.30			
	65	40.3	40.4	40.35			
	66	40.4	40.4	40.40			
	67	40.4	40.4	40.40			
	68	40.4	40.4	40.40			
	69	40.3	40.4	40.35			
	70	40.4	40.4	40.40			
	71	40.4	40.4	40.40			
	72	40.3	40.4	40.35			
	73	40.3	40.3	40.30			
	74	40.3	40.4	40.35			
	75	40.4	40.4	40.40			
	76	40.4	40.4	40.40			
	77	40.3	40.5	40.40			
	78	40.4	40.3	40.35			
	79	40.2	40.4	40.25			
	80	40.2	40.3	40.25			
	81	40.3	40.4	40.35			
	82	40.3	40.4	40.35			
	83	40.3	40.3	40.30			
	84	40.3	40.3	40.30			
	85	40.3	40.4	40.35			
	86	40.3	40.3	40.30			
	87	40.4	40.4	40.40			
	88	40.3	40.4	40.35			
	89	40.3	40.5	40.40			
	90	40.3	40.4	40.35			
	91	40.3	40.3	40.30			

190mm × 268mm
(54g/m2)

[illegible]

190mm × 268mm
(54g/m2)

【 5】

(3 3)

		(V)		(MΩ)		(MΩ)			
		22.9KV	R -	12.05		11,000			
			S -	12.05		11,000			
			T -	12.05		11,000			
			R - S	12.05		11,000			
			T - R	12.05		11,000			
			S - T	12.05		11,000			
	22900/380	1 -	12.05		11,000				
		2 -	0.3		550				
		1 - 2	20		550				
		380	R -	0.3		550			
			S -	0.3		550			
			T -	0.3		550			
			R - S	0.3		550			
			T - R	0.3		550			
			S - T	0.3		550			
				()		()			
		380	R -	0.3		550	550		
			S -	0.3		550	550		
			T -	0.3		550	550		
			R - S	0.3		550	550		
			T - R	0.3		550	550		
			S - T	0.3		550	550		
		367	1 -	1.0		550			
		DC24		1.0	(v) 0.1	12	(v)550		
		DC24		1.0	(v) 0.1	1.7	(v)550		1
		DC24		1.0	(v) 0.1	26	(v)550		2
		380		0.3		550			
		380		0.3		550			
		380		0.3		550			
		380		0.3		550			
		380		1.0	(v) 0.1	550	(v)550		
		380	Blower	1.0		(1)550	(2)550		
		380	Blower	1.0		(3)550	(4)550		

190mm × 268mm
(54g/m2)

【 6】

(3 3)

[illegible]

190mm × 268mm
(54g/m2)

【 7】

(3 3)

[illegible]

()

1. _____.
2. _____.
3. _____, _____, _____.