

( 1 )

1.		4.				
2.		5.		6.	10 X 42	
3.	18	7.	2018-04-04	가	24,211	
* “ ” “ ” “ - ”						
8. ( , )			15.			
9. ( )						
10.			16.	( )		
11.		-	17.			
		-			-	
	( )					
12.						
		-			-	
13.		-	18.			
			19.			
14.		-	20.			
		-	21.			
	( )		22.			
	( )		23.	-		
1. 2. 3.		4. 5.				
1 “ ”			2026 03 10 ~ 2026 03 12			











【 4】 ( 3 2 )

	2026 03 09				( 1 )		
(mm)	40.2	(mm)	40.05		(%)	3.72	
		6 x Fi(25)			(kg/m)	6.13	
	(mm)	40.0 (41.6)	(ton)	119.3	(mm)	2.68	
가	가	2018-04-01			(h)	24,211	
			2	3	4	5	(m)
		(mm)					
	가	( 1 )	( 2 )	( 3 )		(+12% )	(7% )
(가)	1	40.9	41.0	41.10		2.75	.49
	2	40.5	40.9	40.90		2.25	.98
	3	40.2	40.6	40.80		2	1.47
	4	41.1	41.4	41.50		3.75	.96
	5	41.0	41.2	41.50		3.75	1.2
	6	41.0	41.2	41.40		3.5	.97
(200)	1	40.2	40.3	40.25			
	2	40.1	40.2	40.15			
	3	40.1	40.3	40.20			
	4	40.1	40.2	40.15			
	5	40.2	40.2	40.20			
	6	40.1	40.2	40.15			
	7	40.0	40.2	40.10			
	8	40.1	40.1	40.10			
	9	40.0	40.1	40.05			
	10	40.1	40.1	40.10			
	11	40.2	40.2	40.20			
	12	40.1	40.3	40.20			
	13	40.2	40.3	40.25			
	14	40.2	40.3	40.25			
	15	40.1	40.2	40.15			
	16	40.2	40.3	40.25			
	17	40.2	40.3	40.25			
	18	40.2	40.2	40.20			
	19	40.2	40.3	40.25			



【 5】

( 3 2 )

	(V)		(M )	(V)	(M )			
	22.9KV	L1 -	12.05	1,000	2,000			
	22.9KV	L2 -	12.05	1,000	2,000			
	22.9KV	L3 -	12.05	1,000	2,000			
	22.9KV	L1 - L2	12.05	1,000	2,000			
	22.9KV	L3 - L1	12.05	1,000	2,000			
	22.9KV	L2 - L3	12.05	1,000	2,000			
	22,900/380	1 -	12.05	1,000	2,000			
	22,900/380	2 -	1.0	500	550			
	22,900/380	1 - 2	20	500	550			
	380	L1 -	1.0	500	550			
	380	L2 -	1.0	500	550			
	380	L3 -	1.0	500	550			
	380	L1 - L2	1.0	500	550			
	380	L3 - L1	1.0	500	550			
	380	L2 - L3	1.0	500	550			
	380	L1 -	1.0	500	550			
	380	L2 -	1.0	500	550			
	380	L3 -	1.0	500	550			
	380	L1 - L2	1.0	500	550			
	380	L3 - L1	1.0	500	550			
	380	L2 - L3	1.0	500	550			
	380	L1 -	1.0	500	550			
	380	L2 -	1.0	500	550			
	380	L3 -	1.0	500	550			
	380	L1 - L2	1.0	500	550			
	380	L3 - L1	1.0	500	550			
	380	L2 - L3	1.0	500	550			
		367	1 -	25	500	550		
		DC24		10	250	220		
		DC24		1.0	250	220		
		DC24		10	250	220		1
		DC24		1.0	250	220		1
		DC24		10	250	220		2

190mm × 268mm  
( 54g/m2)

	(V)		(M )	(V)	(M )	
	DC24		1.0	250	220	2
	380		1.0	500	550	
	380		1.0	500	550	
	380		1.0	500	550	
	380		1.0	500	550	
	380		25	500	550	
	DC24		1.0	250	220	
	380	Blower	25	500	550	
	380	Blower	25	500	550	
	380	Blower	25	500	550	
	380	Blower	25	500	550	
	380	Heat Exchanger	25	500	550	
	380	Pump Cooler	25	500	550	
	380	Pump Cooler	25	500	550	
					( )	
	380	Cardencing	25	500	550	
	380	Door Opener	25	500	550	
	380	Auxiliary	25	500	550	IN
	380	Auxiliary	25	500	550	OUT
					( )	
	380	Cardencing	25	500	550	
	380	Door Opener	25	500	550	
	380	Auxiliary	25	500	550	IN
	380	Auxiliary	25	500	550	OUT
					( A)	
	380	Cardencing	25	500	550	
	380	Door Opener	25	500	550	
	380	Auxiliary	25	500	550	IN
	380	Auxiliary	25	500	550	OUT
					( B)	
	380	Cardencing	25	500	550	
	380	Door Opener	25	500	550	
	380	Auxiliary	25	500	550	IN
	380	Auxiliary	25	500	550	OUT





